



## Warranty

Pneumadyne guarantees each product against defects in material and workmanship for one year from date of shipment. Because of a policy of constant improvement, Pneumadyne reserves the right to make design changes and improvements in our products at any time without notice or assuming any obligations to incorporate changes and improvements in products previously sold, nor to replace previously sold products with these changes and improvements.

### Warrantied Returns

Any warranty is void if returned product is disassembled or if the configuration has been altered in any way.

### Disclaimer

We make no other warranty, expressed or implied.

### Remedies

If product fails to perform as warranted, Pneumadyne will repair or replace, at our option. We will not assume any liability for consequential damages, labor delays or any other charges.

## Warnings

### Design & Specification

All published information is based on usual manufacturing standards and product applications and is for general reference purposes. Supplied information is in no way a representation of a warranty for product.

### Applications

Pneumadyne, Inc. components are designed for specific applications in pneumatic systems. They are tested with filtered and lubricated air under specified limits of temperature and pressure. For special uses with media other than air, for nonindustrial application or for life support systems, contact Pneumadyne, Inc. for more information. Complying with our specifications will ensure safe and proper installation and operation.

Regulators are for use in industrial compressed air applications only and are not to be used where pressure or temperature can exceed rated operating conditions. See Performance Data.

Pressure indicating and feedback devices such as gauges and transducers must be regularly checked and calibrated to insure accuracy. Calibration should be done prior to installation and at regular intervals. Refer to ANSIB40.1-1974 for standards relating to gauge performance and use. Consult Pneumadyne before using this product with media other than air or in nonindustrial, life support applications.

**Suitability for Application**

It is the responsibility of the specifying and purchasing organization to determine suitability of any Pneumadyne product for a particular application. The customer assumes all risk in the testing and investigating of a product to be used in a specific application.

**Materials Compatibility**

Occasionally lubricants or contaminants found in compressed air systems can attack material used in the manufacture of these components, resulting in product failure. The installer should ensure component materials are compatible with the system.

**High Pressure Level**

Compressed air systems are under a high level of pressure. Any attempt to connect, disconnect or repair these components under these circumstances could result in serious personal injury. Disconnect and vent all pressure sources prior to removal.

**Code Compliance**

Pneumadyne strongly advises that all installation and repair of components be performed by FPS certified personnel. The installer is cautioned to observe all electrical, mechanical and other codes applicable to the installation and operation of these products.

**Repair & Conversion**

Components are required to be checked for leakage and proper function prior to installation and operation if they have been disassembled for repair or if their configuration has been altered.

**Mixed Wastes**

In order for Pneumadyne, Inc. to stay compliant with 40 CFR part 266: Storage, Treatment, Transportation and disposal of Mixed Wastes, and 40 CFR parts 261 and 268 Hazardous Waste Identification Rule (HWIR); Revisions to mixture and Derived from rules, any parts sent back for return to Pneumadyne, Inc. must be cleaned and free from any Media or Chemical upon arrival at our facility.