



Specification Sheet

3-Way Normally Closed Valves with 1/16 Tube ID Input

Performance Data

Temperature Range	Media
-20° to 160° F	Compatible w/ seals

Product Number	Operating Pressure	Series	Cv	Flow (scfm)		Fill sec/in ³ 0-90 psi	Exhaust sec/in ³ 100-10 psi	Actuation Force	
				50 psi	125 psi			50 psi	125 psi
C021605	26" Hg to 125 psi	"200"	.026	.93	2.10	.14	.20	29 oz	51 oz
C021625	26" Hg to 125 psi	"200"	.026	.93	2.10	.14	.20	29 oz	51 oz
C021601	26" Hg to 125 psi	"200"	.026	.93	2.10	.14	.20	6 oz	11 oz
C021621	26" Hg to 125 psi	"200"	.026	.93	2.10	.14	.20	6 oz	11 oz
C021603	26" Hg to 125 psi	"200"	.026	.93	2.10	.14	.20	6 oz	11 oz
C021623	26" Hg to 125 psi	"200"	.026	.93	2.10	.14	.20	6 oz	11 oz
C021607	26" Hg to 125 psi	"200"	.026	.93	2.10	.14	.20	29 oz	51 oz
C021627	26" Hg to 125 psi	"200"	.026	.93	2.10	.14	.20	29 oz	51 oz

When design makes data critical- contact factory for confirmation. All published information is based on usual manufacturing standards and product applications and is for general reference purposes. Supplied information is in no way a representation of a warranty for product.

Materials

"200" Series
Electroless Nickel Plated Brass Body, Buna-N Seals,
Brass Stem and Stainless Steel Spring