



## Specification Sheet

### 3-Way Normally Closed Valves with 1/4 PI Input

#### Performance Data

Temperature Range	Media
-20° to 160° F	Compatible w/ seals

Product Number	Operating Pressure	Series	Cv	Flow (scfm)		Fill sec/in <sup>3</sup> 0-90 psi	Exhaust sec/in <sup>3</sup> 100-10 psi	Actuation Force	
				50 psi	125 psi			50 psi	125 psi
A0-30-6	0 to 125 psi	"O"	.24	8.2	17.3	0.02	0.06	3 lbs	5-1/2 lbs
A3-30-6	0 to 125 psi	"3"	.23	7.2	15.4	0.02	0.04	3-1/2 lbs	6 lbs
A11-30-64	0 to 125 psi	"11"	.29	10.2	22.1	0.01	0.05	3-1/2 lbs	7 lbs
A11-30-66	0 to 125 psi	"11"	.29	10.2	22.1	0.01	0.05	3-1/2 lbs	7 lbs
A11-30-67	0 to 125 psi	"11"	.29	10.2	22.1	0.01	0.05	3-1/2 lbs	7 lbs
H0-30-6	0 to 125 psi	"O"	.24	8.2	17.3	0.02	0.06	4 oz	6 oz
H3-30-6	0 to 125 psi	"3"	.23	7.2	15.4	0.02	0.04	8 oz	14 oz
H11-30-64	0 to 125 psi	"11"	.29	10.2	22.1	0.01	0.05	8 oz	14 oz
H11-30-66	0 to 125 psi	"11"	.29	10.2	22.1	0.01	0.05	8 oz	14 oz
H11-30-67	0 to 125 psi	"11"	.29	10.2	22.1	0.01	0.05	8 oz	14 oz
F0-30-6	0 to 125 psi	"O"	.24	8.2	17.3	0.02	0.06	4 oz	6 oz
F3-30-6	0 to 125 psi	"3"	.23	7.2	15.4	0.02	0.04	8 oz	14 oz
F11-30-64	0 to 125 psi	"11"	.29	10.2	22.1	0.01	0.05	8 oz	14 oz
F11-30-66	0 to 125 psi	"11"	.29	10.2	22.1	0.01	0.05	8 oz	14 oz
F11-30-67	0 to 125 psi	"11"	.29	10.2	22.1	0.01	0.05	8 oz	14 oz

When design makes data critical- contact factory for confirmation. All published information is based on usual manufacturing standards and product applications and is for general reference purposes. Supplied information is in no way a representation of a warranty for product.

#### Materials

##### "0" Series

Anodized Aluminum & Electroless Nickel Plated Brass Body,  
Buna-N Seals, Brass Stem and Stainless Steel Spring

##### "11" Series

Anodized Aluminum & Electroless Nickel Plated Brass Body,  
Buna-N Seals, Brass Stem and Stainless Steel Spring

##### "3" Series

Anodized Aluminum & Electroless Nickel Plated Brass Body,  
Buna-N Seals, Brass Stem and Stainless Steel Spring