



Specification Sheet

Quick Exhaust Valves 5/32" PI Input Port

Performance Data

Temperature Range	Media
-20° to 160° F	Compatible w/ seals

Product Number	Operating Pressure	Series	Cv	Flow (scfm)		Fill Time sec/in3 0-90 psi	Exhaust Time sec/in3 100-10 psi
				50 psi	125 psi		
QE10-7MF	0 to 125 psi	"10"	.15	5.0	10.8	.03	.06
QE11-M-71	0 to 125 psi	"11"	.20	8.2	20.2	.02	.02
QE11-M-74	0 to 125 psi	"11"	.20	8.2	20.2	.02	.02
QE11-M-76	0 to 125 psi	"11"	.20	8.2	20.2	.02	.02
QE11-M-77	0 to 125 psi	"11"	.20	8.2	20.2	.02	.02
QE11-M-78	0 to 125 psi	"11"	.20	8.2	20.2	.02	.02
QE11-P-71	0 to 125 psi	"11"	.20	8.2	20.2	.02	.02
QE11-P-74	0 to 125 psi	"11"	.20	8.2	20.2	.02	.02
QE11-P-76	0 to 125 psi	"11"	.20	8.2	20.2	.02	.02
QE11-P-77	0 to 125 psi	"11"	.20	8.2	20.2	.02	.02
QE11-P-78	0 to 125 psi	"11"	.20	8.2	20.2	.02	.02
QE11-S-71	0 to 125 psi	"11"	.20	8.2	20.2	.02	.02
QE11-S-74	0 to 125 psi	"11"	.20	8.2	20.2	.02	.02
QE11-S-76	0 to 125 psi	"11"	.20	8.2	20.2	.02	.02
QE11-S-77	0 to 125 psi	"11"	.20	8.2	20.2	.02	.02
QE11-S-78	0 to 125 psi	"11"	.20	8.2	20.2	.02	.02

When design makes data critical- contact factory for confirmation. All published information is based on usual manufacturing standards and product applications and is for general reference purposes. Supplied information is in no way a representation of a warranty for product.

Materials

Quick Exhaust Valves

"10" Series: QE10 -
Electroless Nickel Plated Brass Body, Buna-N Seals

"11" Series: QE11-
Anodized Aluminum and Electroless Nickel Plated /
Black Dichromate Brass Body, Buna-N Seals